

GUN BARREL SAFETY LOCK WITH HAND RATCHETING WRENCH

5 This application is a continuation-in-part of prior Application, No. 10/027,034; filed December 20, 2001, which is incorporated by reference herein.

Background of the Invention

10 The present invention relates to the art of gun or firearm safety. It finds particular application in conjunction with barrel locks or plugs, and will be described with particular reference thereto. However, it is to be appreciated that the present invention is also amenable to other like applications.

15 Firearm safety is a concern for most gun owners. In general, gun owners desire a way to secure their firearms from unauthorized use and/or accidental discharge. Accordingly, devices have been developed to achieve this goal. However, many of the prior art devices suffer from various drawbacks and/or limitations.

20 For example, trigger locks have been developed which when properly installed on a gun prevent an unauthorized user from squeezing the gun's trigger. While these trigger locks may prevent a gun's firing mechanism from being intentionally activated, trigger locks generally do not prevent a gun from being loaded. Accordingly, a live round can still be positioned in the firing chamber and a sudden jarring of the gun and/or faulty ammunition can potentially result in the accidental discharge of the weapon.

25 Another safety device for securing firearms is the so called barrel plug which is designed to wedge in and/or otherwise obstruct the gun's barrel. The previously developed barrel plugs also have drawbacks and/or limitation. Many of the prior art barrel plugs cannot easily and quickly be installed and removed. Others are not sufficiently tamper resistant and/or secure. That is to say, the security of some prior art barrel plugs can be frustrated with relative ease by an
30 unauthorized user, e.g., pulling or pushing or otherwise removing the plug from

the barrel. Furthermore, prior art barrel plugs tend to be of limited use insomuch as each only fits one preset caliber or bore size.

While obstructing the barrel, often barrel plugs do not prevent loading of the firearm. This is particularly hazardous when the barrel plug is completely hidden within the barrel. For example, a unsuspecting user, not knowing the barrel plug is installed and not seeing any external evidence of its installation, may load and attempt to fire the gun. Of course, the gun will potentially backfire or otherwise injure the user and/or damage either the firearm or the barrel plug or both.

The present invention contemplates a new and improved gun barrel safety lock with hand ratcheting wrench which overcomes the above-referenced problems and others.

Summary of the Invention

A gun safety device includes a barrel plug assembly having a first compression member, a second compression member, an expansion member, a joining member, and an adjustable extension rod assembly. The expansion member is sandwiched between the first compression member and the second compression member. The joining member is operatively linking the first compression member to the second compression member. The joining member is adapted to draw at least one of the compression members towards the other compression member. The adjustable extension rod assembly extends from the second compression member.

A gun safety device includes a barrel plug assembly having an adjustable rod assembly and a selectively expandable portion. The adjustable rod assembly adjusts the length of the barrel plug assembly. The selectively expandable portion selectively engages the barrel of an associated gun. The adjustable rod assembly includes a tubular extension and a slidable rod received in the tubular extension.

30

Brief Description of the Drawings

The invention may take form in various components and arrangements of components, and/or in various steps and arrangements of steps. The drawings are only for purposes of illustrating preferred embodiments and are not to be construed as limiting the invention.

FIGURES 1A through 1D show side, top, bottom and perspective views, respectively, of an exemplary gun barrel safety lock with an attached hand ratcheting wrench in accordance with aspects of the present invention.

FIGURE 2A shows an exploded side view (with internal features being represented by dashed line) of an exemplary barrel plug assembly in accordance with a preferred embodiment of the present invention and as also shown in FIGURES 1A-1D.

FIGURE 2B shows an exploded perspective view of the barrel plug assembly of FIGURE 2A.

FIGURE 3A shows an exploded perspective view (with internal features being represented by dashed line) of an exemplary hand ratcheting wrench assembly in accordance with a preferred embodiment of the present invention and as also shown in FIGURES 1A-1D.

FIGURES 3B and 3C show side views (with internal features being represented by dashed line) of the hand ratcheting wrench assembly of FIGURE 3A, with an extraction rod locked in the retracted and extended positions, respectively.

FIGURE 3D shows a perspective view of the hand ratcheting wrench assembly of FIGURE 3A with the extraction rod locked in the extended position.

FIGURE 4 shows an exploded perspective view of both the barrel plug and hand ratcheting wrench assemblies of FIGURES 2A and 3A.

FIGURES 5A through 5E show a back, a side, a front and two perspective views, respectively, of a revolver with a barrel plug assembly in accordance with aspects of the present invention installed in the barrel.

FIGURES 6A through 6E show the corresponding views, respectively, of FIGURES 5A through 5E with a wrench assembly attached to the barrel plug assembly in accordance with aspects of the present invention.

FIGURE 7 shows a partially cut away side view corresponding to
5 FIGURE 5B.

FIGURE 8A is an exploded perspective view showing selected internal elements (including an extraction rod, and a slip clutch and ratchet assembly) of the hand ratcheting wrench assembly of FIGURE 3A.

FIGURE 8B is an unexploded perspective view showing selected
10 internal elements (including an extraction rod, and a slip clutch and ratchet assembly) of the hand ratcheting wrench assembly of FIGURE 3A.

FIGURE 9A is a perspective view of an alternative barrel plug assembly.

FIGURE 9B is an exploded view of a portion of the barrel plug
15 assembly of FIGURE 9A.

FIGURE 9C is a perspective view of the barrel plug assembly of FIGURE 9A in an extended position having a key inserted into the barrel plug assembly.

FIGURE 9D is a close-up view of a guide tab and a guide slot of the
20 barrel plug assembly of FIGURE 9A.

FIGURE 9E is a partial cross-section of the barrel plug assembly of FIGURE 9A, (with some internal features being represented by a dashed line.)

FIGURE 10A is an exploded perspective view of another alternative barrel plug assembly.

FIGURE 10B is a close-up view of section A of FIGURE 10A.
25

FIGURE 10C is an assembled partial cross-section of the barrel plug assembly of FIGURE 10A, (with some internal features being represented by a dashed line.)

FIGURE 11A is an exploded perspective view of another alternative
30 barrel plug assembly.

FIGURE 11B is a close-up view of section A of FIGURE 11A.

FIGURE 11C is an assembled partial cross-section of the barrel plug assembly of FIGURE 11A, (with some internal features being represented by a dashed line).

5 FIGURE 12A is an exploded perspective view of another alternative barrel plug assembly.

FIGURE 12B is a close-up view of section A of FIGURE 12A.

FIGURE 12C is an assembled partial cross-section of the barrel plug assembly of FIGURE 12A, (with some internal features being represented by a dashed line.)

10 FIGURE 13A is a perspective view of an adjustable barrel plug assembly having bore adjusting components mounted thereto.

FIGURE 13B is an exploded view of FIGURE 13A.

FIGURE 14A is a partial cross-section of a barrel plug assembly including a flexible joint.

15 FIGURE 14B is a close-up view of section A of FIGURE 14A, (with some internal features being represented by a dashed line.)

Detailed Description of the Preferred Embodiment(s)

20 With reference to the FIGURES, in particular FIGURES 1A-1D and 4, an exemplary gun barrel safety lock with hand ratcheting wrench in accordance with a preferred embodiment of the present invention includes a barrel plug assembly A (see also FIGURES 2A and 2B) and a selectively detachable hand ratcheting wrench assembly B (see also FIGURES 3A-D) which is used to selectively install and uninstall the barrel plug assembly A in the barrel of a
25 firearm. The barrel plug assembly A is readily adaptable and may be installed in any firearm regardless of type (i.e., handgun, rifle, shotgun or otherwise), barrel length, the existence of a flash guard, caliber, gauge or bore diameter, number of barrels, or method of loading. With the plug assembly A installed, the barrel of the firearm is blocked and the firearm is therefore secured from unauthorized
30 operation insomuch as the plug assembly cannot be removed without the corresponding hand ratcheting wrench assembly B. Additionally, an optional plug

extension **24** which is part of the plug assembly **A** will prevent the firearm from having a round of ammunition loaded in the firing chamber, aligned with the barrel, or otherwise placed in a firing position. Moreover, in accordance with preferred embodiments, the barrel safety lock is very compact and rugged.

5 The barrel plug assembly **A** is installed in the bullet exit end or muzzle of a gun barrel. As best seen in FIGURES **2A** and **2B**, the barrel plug assembly **A** is made up of eight components identified by reference numbers **10-24**. A bolt **10** includes opposing threaded **10a** and head **10b** ends. The head **10b** is preferably a male hexagon or other like key that is matched or mated to a socket **90b** of an extraction rod **90** included in the wrench assembly **B** (see, e.g., FIGURES **3A-3D** and **4**). Optionally, the head **10b** and the socket **90b** are uniquely matched or mated so that no other combination of head **10b** and socket **90b** will properly fit together with one another. In this manner, only the socket **90b** of the wrench assembly **B** which was intended for use with a given plug assembly **A** will fit that plug assembly's bolt head **10b**, and hence, only that wrench assembly **B** will be able to operate (i.e., turn) the bolt **10**. In this case, there exists a one-to-one correspondence between the bolt head **10b** and the socket **90b** of each plug/wrench assembly pair. Alternately, there may not be a one-to-one correspondence therebetween. Rather, there may be a limited number of bolt head configurations that match corresponding socket configurations. Optionally, the number of configurations is large enough so that it is statistically unlikely that a randomly selected socket **90b** would fit together with a given bolt head **10b**.

25 In a preferred embodiment, the bolt **10** includes a bushing **10c** which has a diameter larger than the bolt shaft **10d** on which the threads **10a** are formed. Preferably, the bolt **10** is formed from stainless steel or other similar metal or material. The bolt head **10b** includes a hexagonal or other key shaped region **10b'** which lies beneath a protrusion or smooth stub **10b''**. Consequently, for the socket **90b** to mate with the key portion **10b'** of the bolt head **10b** it has a matching recess which accepts the smooth stub **10b''** when the bolt head **10b** is received in the socket **90b**.

A flanged bolt-retaining plug **12** is bonded to an expansion tube **14** which is in turn bonded to a threaded rear compression base **16**. With respect to a central longitudinal axis **z**, the flanged bolt-retaining plug **12** includes a longitudinally extending cylindrical member **12a** and a radially extending flange **12b** at a first end thereof. The flanged bolt-retaining plug **12** is sized to and does receive and retain the bolt **10**. An inner diameter of the cylindrical member **12a** is two tiered. That is, the inner diameter of the cylindrical member **12a** is tiered or stepped down to create an annular surface which is substantially normal to the axis **z**. The larger inner diameter of the cylindrical member **12a** is sized to and does receive the bushing **10c** of the bolt **10**. The smaller inner diameter of the cylindrical member **12a** is less than the outer diameter of the bushing **10c**. The smaller inner diameter is sized to and does receive the shaft **10d** of the bolt **10**. In this manner, when the bolt **10** is inserted through the flanged bolt-retaining plug **12**, the normal annular surface (created by the two tiered inner diameter of the cylindrical member **12a**) abuts the bushing **10c** thereby restricting the bolt **10** from passing longitudinally beyond a designated point with respect to the flanged bolt-retaining plug **12**.

Preferably, the flanged bolt-retaining plug **12** is made of brass or other like metal or other similarly hard, durable and/or rigid material. The flange **12b** is preferably a plate which is substantially normal to the axis **z**. The perimeter and thickness of the plate are shaped and sized to be selectively engaged non-rotatably with a flange receiving portion **50a** of a lower handle mount **50** included in the wrench assembly **B** (see, e.g., FIGURE 4). Optionally, the flange **12b** and the flange receiving portion **50a** are uniquely matched or mated so that no other combination of flange **12b** and flange receiving portion **50a** will properly fit together with one another. In this manner, only the flange receiving portion **50a** of the wrench assembly **B** which was intended for use with a given plug assembly **A** will fit that plug assembly's flange **12b**, and hence, only that wrench assembly **B** will be able to properly align with the plug assembly **A** and hold the flanged bolt-retaining plug **12** (and other components rotationally fixed thereto) rotationally fixed with respect to the lower handle mount **50**. In this case, there exists a one-

to-one correspondence between the flange **12b** and the flange receiving portion **50a** of each plug/wrench assembly pair. Alternately, there may not be a one-to-one correspondence therebetween. Rather, there may be a limited number of flange configurations that match corresponding flange receiving configurations.

5 Optionally, the number of configurations is large enough so that it is statistically unlikely that a randomly selected flange receiving portion **50a** would fit together with a given flange **12b**.

It is to be noted that the combinations of wrench assemblies **B** and plug assemblies **A** that will permit the selective installing and uninstalling of any
10 given plug assembly **A** in a firearm barrel is able to be limited inasmuch as for the combination to cooperate both the flange **12b** and flange receiving portion **50a** have to match and the bolt head **10b** and the socket **90b** have to match.

The expansion tube **14** is a cylindrical member preferably made of rubber or other like material which expands radially when compressed
15 longitudinally and contracts radially when stretched longitudinally. A first end of the expansion tube **14** is bonded to the second end **12c** of the cylindrical member **12a** opposite the flange **12b**. A first end of the compression base **16** is bonded to the second end of the expansion tube **14** opposite the flanged bolt retaining plug **12**. In this manner, the flanged bolt-retaining plug **12**, the
20 expansion tube **14** and the compression base **16** are all rotationally fixed with respect to one another. The bolt shaft **10d** extends entirely through the inner diameter of the expansion tube **14** such that the threads **10a** may be engaged with the compression base **16**. The length of the bolt shaft **10d** is preferably at least long enough to allow the expansion tube **14** to be longitudinally-
25 uncompressed while the threads **10a** are still engaged with the compression base **16** and the bushing **10c** abuts the annular surface created by the two tiered inner diameter of the cylindrical member **12a**.

The compression base **16** is also preferably made from brass or another suitable metal or like material. The first end of the compression base **16**
30 (i.e., the end proximate the expansion tube **14**) has a threaded inner diameter arranged to receive the threaded end **10a** of the bolt **10**. The second end is

threaded or otherwise arranged to receive a screw-on expansion tube adapter **18** if the slide-on expansion tube **20** is being employed. Alternately, the plug extension **24** may be affixed to the second end of the compression base **16**.

When the caliber, bore or otherwise the inner diameter of the barrel in which the plug assembly **A** is to be installed is essentially the same or some determined amount larger than the outer diameter of the longitudinally-uncompressed expansion tube **14** (which is substantially equal to the outer diameter of the compression base **16** and the cylindrical member **12a**), then the bore adjusting components **C** (i.e., one-way locking push nut **22**, slide-on expansion tube **20** and screw-on expansion tube adapter **18**) are not used. Alternately, if the barrel bore is significantly larger, then the bore adjusting components **C** are used.

Essentially, there is a set of bore adjusting components **C** for each caliber or barrel bore diameter in which the plug assembly **A** may be installed. After determining the caliber or bore of the barrel in which the plug assembly **A** is to be installed, a user simply selects the set of bore adjusting components **C** designate for that barrel's inner diameter size or caliber. The outer diameters of the bore adjusting components **C** are substantially equal to or less than the inner diameter of the barrel in which they are intended to be used. The inner diameters of the one-way locking push nut **22** and slide-on expansion tube **20** allow them to fit snugly over the outer diameters of the cylindrical member **12a**, the longitudinally-uncompressed expansion tube **14** and the compression base **16**.

Preferably, the expansion tube **14** and the sets of bore adjusting components **C** each fit a range of calibers or bore sizes. That is to say, as compared to O-rings and the like, the tubes **14** and **20** have a greater range of and/or capacity for radial expansion when longitudinally compressed. Accordingly, each individual tube size can fit and wedge into a number of different calibers or bore sizes.

Most preferably, between the tube **14** and one set of bore adjusting components **C** all calibers or bore sizes can be accommodated. In this case, the maximum radial expansion of the tube **14** is large enough to sufficiently wedge

the plug assembly **A** in all barrels having inner diameters substantially equal to or less than the longitudinally-uncompressed outer diameter of the tube **20**. The bore adjusting components **C** are therefore used when the inner diameter of the barrel is substantially equal to or greater than the outer diameter of the tube **20**.

5 The one-way locking push nut **22** is preferably bonded to the first end of the slide-on expansion tube **20**. When used, the combination is slid over the outside of the cylindrical member **12a**, the longitudinally-uncompressed expansion tube **14** and the compression base **16**. The combined length of the one-way locking push nut **22** and the slide-on expansion tube **20** is substantially
10 equal to the combined length of the cylindrical member **12a**, the longitudinally-uncompressed expansion tube **14** and the compression base **16**. The bulbous screw-on expansion tube adapter **18** is sized so as not to fit through the inner diameter of the slide-on expansion tube **20**, and the adapter **18** is preferably screwed onto the second end of the compression base **16** behind the second
15 end of the slide-on expansion tube **20**. Optionally, the adapter **18** may otherwise be attached to the compression base **16**. When the bore adjusting components **C** are used then the plug extension **24** is affixed to the adapter **18**.

 Preferably, the adapter **18** is made out of brass or another metal or like material and the slide-on expansion tube **20** is made of the same or similar
20 material as the expansion tube **14**. The one-way locking push nut **22** is preferably made from spring steel or the like and the plug extension **24** is preferably a vinyl coated steel tension spring or the like. Alternately, the plug extension **24** may be a rigid member.

 To affect installation, the distal end of the plug assembly **A** (with the
25 expansion tube **14** and optional slide-on expansion tube **20** both being longitudinally uncompressed) is inserted into the bullet exit end of the barrel or muzzle of the firearm which is to be secured. As used herein the distal end of the plug assembly **A** refers to the end of the plug assembly **A** opposite the flange **12b**. Preferably, the flange **12b** is larger than the inner diameter of the barrel and
30 hence limits the depth to which the plug assembly **A** is inserted. That is to say,

the flange **12b** remains outside the barrel, preferably, abutting the end of the barrel through which the plug assembly **A** was inserted.

Using the hand ratcheting wrench assembly **B**, the bolt **10** is rotated in a first direction (e.g., clockwise) relative to the flanged bolt-retaining plug **12** which is held rotationally fixed with the flange receiving portion **50a** of a lower handle mount **50** included in the wrench assembly **B**. Inasmuch as the expansion tube **14** and the compression base **16** are rotationally fixed with respect to the flanged bolt-retaining plug **12**, they are also rotationally fixed relative to the rotating bolt **10**. Accordingly, due to the threaded engagement between the compression base **16** and the bolt **10** and the bushing **10c** abutting the substantially normal annular surface created by the two tiered inner diameter of the cylindrical member **12a**, the relative rotation of the bolt **10** with respect to the compression base **16** causes the compression base **16** and the flanged bolt-retaining plug **12** to be drawn together thereby longitudinally compressing the expansion tube **14** therebetween. Likewise, if the bore adjustment components **C** are being used, the screw-on expansion tube adapter **18** is drawn with the compression base **16** toward the flanged bolt-retaining plug **12** thereby longitudinally compressing the slide-on expansion tube **20** therebetween.

The longitudinal compression of the expansion tube **14** causes the expansion tube **14** to bulge or radially expand and/or wedge against the inner diameter of the barrel in which it was inserted thereby securing the plug assembly **A** in the same. Alternately, if the slide-on expansion tube **20** is being employed, the expansion tube **14** bulges and/or applies a radially extending force outwardly against the inner diameter of the slide-on expansion tube **20**. At the same time, the slide-on expansion tube **20** will bulge or radially expand and/or wedge against the inner diameter of the barrel in which it was inserted. The dual wedging of the expansion tubes **14** and **20** prevents the barrel plug assembly **A** from being removed. In either case, the hand ratcheting wrench assembly **B** may then be removed, and absent access to the corresponding wrench assembly **B**, the firearm is now secured from unauthorized use.

To uninstall the plug assembly **A** from a barrel, the hand ratcheting wrench assembly **B** is re-engaged with the plug assembly **A** and used to rotate the bolt **10** in a second direction opposite the first (e.g., counterclockwise) while the flanged bolt-retaining plug **12** is held rotationally fixed with the flange receiving portion **50a** of a lower handle mount **50** included in the wrench assembly **B**. Again, inasmuch as the expansion tube **14** and the compression base **16** are rotationally fixed with respect to the flanged bolt-retaining plug **12**, they are also rotationally fixed relative to the rotating bolt **10**. This time, however, the opposite relative rotation of the bolt **10** with respect to the compression base **16** releases the longitudinal compression applied to the expansion tube **14**. Likewise, if the bore adjustment components **C** are being used, the longitudinal compression applied to the slide-on expansion tube **20** is also released. Upon the release of the longitudinal compression to the expansion tube **14** and/or the slide-on expansion tube **20**, the bulge or radially expansion therein and/or the radial force exerted thereby subsides and the plug assembly **A** is no longer wedge against the inner diameter of the barrel in which it was inserted thereby freeing it for extraction from the same by pulling on the flange **12b** with the hand ratcheting wrench assembly **B**. Then, if desired, the wrench assembly **B** may be detached from the plug assembly **A**. Alternately, the wrench assembly **B** may be detached prior to extracting the plug assembly **A** and the plug assembly **A** extracted by pulling on the flange **12b** by hand. In either case, the firearm is now unsecured and ready for use.

It is to be appreciated that to prevent unwanted twisting and/or turning of various components while the bolt **10** is being rotated, the threaded rear compression base **16** and the flanged bolt-retaining plug **12** are bonded to the expansion tube **14**. The screw-on expansion tube adapter **18** is also mechanically connected to the compression base **16** and therefore it is also rotationally fix with respect to the flanged bolt-retaining plug **12** which is held against rotation while the bolt **10** is being turned. Preferably, the slide-on expansion tube **20** is bonded to the screw-on expansion tube adapter **18** and the one-way locking push nut **22** is bonded to the slide-on expansion tube **20**. All of

the above mentioned bonded and affixed points cooperate not only to prevent each part from twisting and/or turning undesirably, they also give the barrel plug assembly's expansion tubes **14** and/or **20** the ability to be stretched and/or elongated when the bolt **10** is rotated to remove the barrel plug assembly **A** from the barrel. The aforementioned stretching and/or elongating is advantageous insomuch as it encourages the radial contraction of the expansion tubes **14** and/or **20** which might otherwise remain completely or partially expanded due to the shape memory characteristics of the material from which they are made. That is to say, if an elastic tube is longitudinally compressed for an extended period of time and then released, the elastic tube may not immediately relax and/or return to its original radial dimension on its own. Accordingly, there may be a tendency for the plug assembly **A** to remain somewhat wedged in the barrel and therefore its extraction from the barrel may be correspondingly hampered. However, in accordance with a preferred embodiment of the present invention, the relative bonding of the plug assembly components ensures that loosening of the bolt **10** will elongate and/or longitudinally stretch the expansion tubes **14** and/or **20** thereby encouraging their radial contraction which in turn facilitates quick and easy extraction of the plug assembly **A** from the barrel.

Of course, the longitudinal stretching is only achieved when the compression between the flanged bolt-retaining plug **12** and the base **16** is released via a loosening of the bolt **10**. That is to say, so long as the bolt **10** continues to hold the flanged bolt-retaining plug **12** and the base **16** drawn together, pulling on the flange **12b** will not stretch or elongate the expansion tubes **14** and/or **20**. In this manner, the degree to which the plug assembly **A** is wedged in the barrel is not lessened by merely pulling on the flange **12b** without first untightening the bolt **10**. Accordingly, security is not compromised by this feature.

It is to be appreciated that with the extension rod **90** locked in the extended position and the tabs **54** (described later herein) holding the flange **12b** in the receiving portion **50a** of the lower handle mount **50**, the bolt **10** is kept from pushing out of the bolt-retaining plug **12** when it is loosened. The bushing **10c**

acts as a step such that the top of the bushing **10c** will press against the bottom of the extraction rod's socket **90b**. Consequently, loosening of the bolt **10** pushes the bolt-retaining plug **12** and the compression base **16** apart from one another and longitudinally elongates the tube **14** (and tube **20** if used) thereby radially contracting the same.

The flanged bolt-retaining plug **12** serves a number of purposes. It is used to prevent the barrel plug assembly **A** from being forced through the barrel, and it keeps the bolt **10** and the slide-on expansion tube **20** aligned within the assembly. The flanged bolt-retaining plug **12** also prevents the bolt **10** from being tampered with inasmuch as the bolt **10** is recessed therein. The flange **12b** also provides a means to hold desired plug assembly parts rotationally fixed while the bolt **10** is being turned. The flanged bolt-retaining plug **12** gives both the expansion tube **14** and the slide-on expansion tube **20** a compression point. The flange **12b** is also used as an attachment point for the hand ratcheting wrench assembly **B**.

In addition to wedging the plug assembly **A** into the muzzle end of the firearm's barrel, the rest of the barrel will contain and/or be blocked by the plug extension **24** which may be optionally a rigid member or a tension spring (optionally, vinyl coated) or the like. Preferably, the plug extension **24** is long enough to extend into and/or through the loading chamber or the action/receiver portion of the firearm. Consequently, after the barrel plug assembly **A** has been locked into place, the plug extension **24** will not permit the firearm to be loaded.

Consider, for example, a revolver **200** having a barrel **210** and cylinder **220** (see, e.g., FIGURES **5A** through **7**). The plug assembly **A** may be locked into place when the revolver's cylinder **220** is removed from its firing position (not shown). With the plug extension **24** preferably extending into the cylinder housing, the cylinder **220** is prevented from being returned to the firing position and therefore a chamber in the cylinder **220** cannot be aligned with the barrel **210** or firing mechanism. Alternately, the plug assembly **A** may be installed when an empty cylinder chamber is in the firing position, e.g., as shown in FIGURE **7**. With the plug extension **24** preferably extending into a cylinder chamber, the

cylinder **220** cannot therefore be removed for loading. Even if other chambers may be loaded without removing the plug assembly **A**, the cylinder **220** cannot be rotated to bring the loaded chamber into alignment with the barrel **210** and firing mechanism.

5 Preferably, the plug extension **24** is mechanically connected to the end of the compression base **16** (or the end of the screw-on expansion tube adapter **18**, if used) so that it cannot be forcibly removed from the barrel.

As noted previously, the specially keyed bolt **10** prevents an individual from loosening the plug assembly **A** without the designated wrench assembly **B**.

10 In a preferred embodiment, the bolt **10** has a head **10b** which is designed with a smooth stud **10b''** that protrudes from above the hexagonal or otherwise keyed portion **10b'**. This combination of stud and keyed portion prevents an individual from loosening or unscrewing the bolt **10** and releasing plug assembly **A** from the barrel without the socket **90b** that fits over the stud **10b''** while mating up with
15 keyed portion **10b'**.

The bolt's bushing **10c** also serves a number of purposes. For example, it facilitates easy engagement of the hand ratcheting wrench's extraction rod **90** (see, e.g., FIGURE 4), it aids alignment and it is used as a pressure contact point. The bushing **10c** is preferably arranged directly under the
20 bolt head **10b** and is an integral part of the bolt **10**. It aids in keeping the bolt head **10b** centered and aligned with the central axis **z** within the inner diameter of the flanged bolt-retaining plug **12**. This centering/alignment ensures that the hand ratcheting wrench's extraction rod **90** can be readily and accurately engaged with and/or disengaged from the bolt head **10b** which is located in the flanged bolt-
25 retaining plug **12**.

Preferably, there is a close tolerance fit between the outer diameter of the bushing **10c** and the larger inner diameter of the cylindrical member **12a** and between the bushing's interface with the normal annular surface created by the two tiered inner diameter of the cylindrical member **12a**. This helps prevent the
30 expansion tube **14** and the rear compression base **16** from bending out of alignment when the expansion tube **14** is compressed. The bushing **10c** is also

used as a contact point as it presses against the normal annular surface created by the two tiered inner diameter of the cylindrical member **12a** when the bolt **10** is tightened to lock or wedge the barrel plug assembly **A** in the barrel.

The flanged bolt-retaining plug **12** has a number of noteworthy features. The flange **12b** serves as a stop, is preferably slim line and compact, can fit any barrel size and is tamper resistant. The flange **12b** is used as a "stop." The flange **12b** will not permit the barrel plug assembly **A** to be forcibly pushed through the barrel's bore. It will also visually indicate if the barrel plug assembly **A** has been installed, and it ensures installation at the proper depth in the barrel's bore. Preferably, when properly installed, the bottom or under side of the flange **12b** butt against the firearm's muzzle or flash guard. As used here, the bottom or under side refers to the side of the flange **12b** which is proximate the cylindrical member **12a**.

The flange's shape mates with and is held by the hand ratcheting wrench's lower handle mount **50** (see, e.g., FIGURES **1A-1D** and **4**). The flange **12b** can therefore be held against rotation. This prevents components rotationally fixed with respect to the flange **12b** (e.g., the rear compression base **16**) from rotating and/or turning when the hand ratcheting wrench assembly **B** applies a torque to the barrel plug assembly's bolt **10**.

In a preferred embodiment, the flange **12b** has a slim line and/or compact face, so that two or more of the barrel plug assemblies **A**, with the same or different calibers, can be mounted side by side in firearms with double barrels. See, e.g., the short dimension **w** shown in FIGURE **2B**.

If an excessive prying force or torque is applied to the flange **12b**, the flange **12b** is preferably designed to break away from the rest of the flanged bolt-retaining plug **12**. This breakaway design is achieved in one preferred embodiment by machining a small groove **12b'** (e.g., 0.500 inch in diameter, 0.063 inch wide and 0.062 inch deep) on the under side of the flange **12b** and centered around the outer circumference of the cylindrical member **12a**. Given an exemplary outer diameter of 0.200 inches for the cylindrical member **12a**, and the 0.500 inch diameter of the portion of the flange **12b** that remains after the rest

has been forcibly broken off, there will remain a 0.150 inch flange shoulder (i.e., $(0.500-0.200)/2 = 0.150$). This 0.150 inch shoulder not only prevents the barrel plug assembly **A** from compromising any of its design and/or safety integrity, but also prevents an unauthorized individual from forcibly removing (by pushing and/or prying) the locked barrel plug assembly **A** from the barrel in which it is installed. That is to say, the shoulder is significant enough to prevent the plug assembly **A** from being pushed through the barrel, but not significant enough for someone to grab a hold of and/or use for leverage to pull the plug assembly **A** from the muzzle.

The flange **12b** is also used as a stop and compression point for the slide-on expansion tube **20** and one-way locking push nut **22**. That is to say, the flange **12b** prevents them from moving forward, away from or out of the muzzle of the firearm, when the bolt **10** is tightened.

The taper end **12c** of the flanged bolt-retaining plug **12** facilitates the installation and removal of the barrel plug assembly **A**. The tapered end **12c** is mated to and "permanently" bonded with (e.g., via chemical bonding, adhesive or the like) one of the tapered ends **14a** of the expansion tube **14**. The tapered end of both parts, when combined, produce a greater bonding surface area and a stronger bond therebetween. This increases the ability of the expansion tube **14** to longitudinally compress or stretch and also prevents it from twisting/turning when a torque is applied to bolt **10** and the flanged bolt-retaining plug **12** is held rotationally fix. The greater bonding area, produced by the tapered ends, is particularly advantageous when the expansion tube **14** is stretched or elongated because, it will facilitate the removal of the barrel plug assembly **A** from the barrel. As previously pointed out, the stretching/elongating of the expansion tube **14**, and hence radially contracting the same, is useful because if an elastic tube is compressed for an extended period of time and then released, the elastic tube may not immediately relax and return to its original condition/dimension. If the tube does not return to its original condition/dimension on its own, it may cause the uncompressed elastic tube, or in this case, the expansion tube **14** to interfere/press against the inner diameter of the firearm barrel. Without

longitudinally stretching/elongating the expansion tube **14**, and hence radially contracting the same, it may be difficult to remove the barrel plug assembly.

Alternately, instead of using the tapered end and, e.g., chemically bonding between the flanged bolt-retaining plug **12** and the expansion tube **14**, a
5 longitudinally notched, annularly ribbed or like patterns or configurations are used in conjunction with a press fitting. The joint or connection thus formed is maintained via mechanical interference and/or the press fitting. This prevents the relative rotation of the joined parts. To keep the ends from separating, when the expansion tube **14** is stretched or elongate, a one-way locking push nut (e.g.,
10 similar to the one-way locking push nut **22**) is optionally molded into the end of the expansion tube **14**. The push nut is, e.g., made of spring steel with inward bent tabs. The tabs are bent in the same direction approximately 45 degrees out from the center of the push nut. In addition, the tabs are preferably equally spaced around the spring steel push nut's inner diameter. As the tabs
15 engage/bends around the shaft/outer diameter of the flanged bolt-retaining plug **12**, the spring steel push nut will grab onto the flanged bolt retaining plug and will not allow the expansion tube **14** to pull off of the flanged bolt-retaining plug **12**.

It is to be noted that, optionally, in any of the same manners that the expansion tube **14** is affixed to the flanged bolt-retaining plug **12** it may also be
20 affixed to the rear compression base **16**.

In a preferred embodiment, the fit and clearance between the flanged bolt-retaining plug **12** and the specially keyed bolt **10** provides self alignment and tamper resistance. The flanged bolt-retaining plug **12** is designed so that the bolt **10** slides into its bore which is, e.g., 0.140 inches in diameter on the top or
25 exposed side of the flange **12b**. As used here the top or exposed side refers to the side or face of the flange **12b** opposite of the cylindrical member **12a**. To keep the bolt **10** from sliding all the way through the bolt-retaining plug **12**, a fixed bushing **10c** attached to or integrated with the bolt **10** abuts against the ledge or substantially normal annular surface created by the two tiered inner diameter of
30 the cylindrical member **12a**. The tolerances between the flanged bolt-retaining plug's bore diameter and the depth of the ledge, and the diameter of the bushing

10c and the distance from the bottom of the bushing **10c** to the top of the stud **10b"** is all arranged and/or maintained so that the barrel plug assembly **A** and the removable hand ratcheting wrench assembly **B** will work properly and provide a secure and tamper resistant device.

5 Preferably, the bolt **10** and the flanged bolt-retaining plug's hole or inner bore are slip fit toleranced so that the bolt **10** is essentially only able to move up or down along and/or in a rotational direction in relationship to the flanged bolt-retaining plug's center line or the axis **z**. In the flanged bolt-retaining plug **12**, the combination of an axially normal ledge or annular surface and a
10 longitudinal constraint (i.e., the wall of the bore), the barrel plug assembly **A** is substantially self aligning. Additionally, the axially normal ledge or annular surface is used as a contact point and as a longitudinal constraint for the bushing **10c**. In one preferred embodiment, the axially normal ledge or annular surface is arranged at such a depth that the bolt rests approximately 0.25 inches below the
15 top surface of the flange **12b**. Accordingly, an individual without the hand ratcheting wrench assembly **B** will not be able to grab or hold onto the bolt head **10b** due to the combined 0.25 inch depth and 0.140 inch diameter hole clearance.

 The expansion tube **14** is preferably made from a petroleum resistant
20 polymer synthetic elastomer material that has good compressive and tension characteristics. The tapered ends **14a** of the expansion tube **14** are preferably chemically bonded, permanently, to the tapered end **12c** of the flanged bolt-retaining plug **12** and the tapered end **16a** of the rear compression base **16**. The small diameter of the parts make the tapered end advantageous. The tapered
25 ends permit a greater bonding area which in turn translates into a stronger bond and hence the advantages attendant thereto. The length of the expansion tube **14** also provides a larger gripping area. That is to say, the expansion tube's length provides a larger contact/gripping area and when longitudinally compressed creates a greater outside diameter, as compared to, e.g.,
30 conventional "O" rings. This feature enables the barrel plug assembly **A** to work with a range of different firearm calibers and/or bore diameters. However, for

firearms with calibers or bore diameters too large for the expansion tube **14** to wedge up against itself, the slide-on expansion tube **20** may be used.

The distal end threaded rear compression base **16** is arranged to mate either with the screw-on expansion tube adapter **18** or the plug extension **24**.

5 Such versatility allows an individual to use barrel plug assembly **A** with different calibers or barrel bore diameter. The screw-on expansion tube adapter **18** is designed to quickly screw on to the back of the threaded rear compression base **16**. This screw-on feature allows the barrel plug assembly **A** to be quickly and easily converted to a larger caliber/diameter (by selecting bore adjustment
10 components **C** with varying outer diameters) without having to change the entire base assembly (i.e., elements **10-16** and **24**). The plug extension **24** (optionally, rigid or tension spring) can also be screwed into the threaded rear compression base **16** or otherwise attached thereto by suitable means. Again, this screw-on feature allows the barrel plug assembly **A** to be quickly and easily converted to
15 accommodate varying barrel lengths (by selecting plug extension **24** with varying lengths) without having to change out the entire base assembly.

The screw-on expansion tube adapter **18** is preferably designed to quickly screw-on to the back of the threaded rear compression base **16** when selected for use and the plug extension **24** can then be screwed into the tapered
20 side of the expansion tube adapter **18**.

In one preferred embodiment, the tapered end **18a** of the expansion tube adapter **18** is bonded to the tapered end **20a** of the slide-on expansion tube **20**. Both parts are affixed together so that the slide-on expansion tube **20** can be effectively compressed or stretched/elongated, and be prevented from twisting.
25 Again, to produce a stronger bonded area between both of the parts, the mated ends of the expansion tube adapter **18** and the slide-on expansion tube **20** are arranged with a tapered fit. The expansion tube adapter **18** preferably also has an approximately 45 degree chamfered distal end that is used to help guide the barrel plug assembly **A** into the muzzle during the installation process.

30 The plug extension **24** prevents the firearm from being loaded, which in turn, makes the weapon inoperable. In accordance with preferred embodiments,

the plug extension **24** is optionally a rigid member or a tension spring. It is arranged to be readily attached to or screwed on to the tapered end of the screw-on expansion tube adapter **18** if employed, or alternately, to the threaded rear compression base **16**.

5 The rigid plug extension **24** is arranged so that the extension **24** will not be able to be removed from the barrel plug assembly through the rear or breech of a firearm. That is to say, the length and inflexibility of the rigid plug extension **24** prevents it from being bent and/or pulled out laterally and/or rearwardly through the breach of the firearm. In a preferred embodiment, this
10 rigid plug extension **24** will be available in a single length which will be cut to fit each respective barrel length. The rigid plug extension **24** enables the barrel plug assembly **A** to be lengthened so that it will be able to block the entire barrel of a firearm. The rigid plug extension **24** may be made of any lightweight material including aluminum, brass, fiberglass, semi-hard or hard rubber or the like. The
15 lightweight material preferably has certain material characteristics such that, e.g., the material will not compress, is light-weight, has a minimal deflection and is soft enough not to scratch the barrel's inner bore.

 The tension spring version of the plug extension **24** is preferably also arranged to be irremovable from the barrel plug assembly through the rear or
20 breech of a firearm, and will preferably come in a single size that is cut to length for a particular firearm. The tension spring is preferably made of a heavy gauge galvanized steel wire and is shaped into a tight continuous-length closed-pattern spring that is vinyl covered and semi-flexible. The vinyl cover will protect the barrel from being scratched when the barrel plug assembly **A** is installed or
25 removed from the barrel. When using the plug extension tension spring **24** with the barrel plug assembly **A** in a gun with a very long barrel, the flexibility of the tight continuous-length closed-pattern extension spring design will aid in the installation and removal of the barrel plug assembly **A**. The spring can also be curled up for easy storage. Accordingly, the user will not have to struggle with a
30 small diameter long solid rod that could get bent or broken during installation, removal or storage.

The tapered end **20a** of the slide-on expansion tube **20** that mates with the face of the one-way locking push nut **22** is preferably chemically or otherwise bonded thereto. The bonded ends preferably have an approximately 45 degree chamfer radius that produces a greater chemical bonding area therebetween.

5 This creates a stronger bond and hence the advantages attendant thereto are achieved, e.g., the bonding strength for effectively compressing or stretching/elongating the tube **20**, and to prevent it from twisting/turning when a torque is applied to the bolt **10**.

10 A selection of slide-on expansion tubes **20** with varying outer diameters allows versatile use of the barrel plug assembly **A**. Particular slide-on expansion tubes **20** can be installed over the original barrel plug assembly (i.e., elements **12-16**) to quickly, easily and inexpensively convert the original barrel plug assembly's smaller outer diameter to a larger outer diameter. This convenient conversion gives the gun owner the ability to use the same barrel
15 plug assembly **A** in any firearm regardless of bore or the barrel's inner diameter.

The size and tolerance of the slide-on expansion tube's inner diameter is noteworthy with respect to the design and versatility of the barrel plug assembly **A**. Preferably, the slide-on expansion tube's inner diameter is designed to have a close slip fit tolerance, when installed over the original barrel plug
20 assembly's cylindrical body. This close slip fit tolerance is arranged so that when the bolt **10** is tightened, not only will it cause the expansion tube **14** to longitudinally compress and bulge out, but it will also cause the slide-on expansion tube **20** to simultaneously longitudinally compress and bulge out. Since the expansion tubes **14** and **20** have such a close slip fit tolerance, the
25 bulging out of the expansion tube **14** will immediately start to push radially outward on the slide-on expansion tube's inner diameter. This radial outward force helps lock the expansion tube **14** to the slide-on expansion tube **20** in the form of an interference fit. This interference fit resists the expansion tubes **14** and **20** from being forcibly separated when the barrel plug assembly **A** is installed.
30 Also, the slide-on expansion tube **20** is made to have a more uniform distribution of radial and compressive forces exerted on the inner diameter on the firearm's

bore. These uniformly distributed forces provide a tighter wedging force between the barrel and the slide-on expansion tube **20**.

The slide-on expansion tube's long length also provides a larger contact/gripping area which is advantageous for larger caliber firearms and when compressed creates a greater outside diameter as compared to conventional "O" rings. The slide-on expansion tube's long length and greater contact/gripping area, will preferably not increase the overall length of the barrel plug assembly **A** due to the fact that the slide-on expansion tube **20** slides over substantially the entire combined length of the metal threaded rear compression base **16**, the rubber expansion tube **14** and the cylindrical member **12a** of the metal flanged bolt-retaining plug **12**. The stop that the flanged bolt-retaining plug **12** provides, and the larger contact/gripping area that the slide-on expansion tube **20** provides, enable the barrel plug assembly **A** to work with all ranges of gun calibers without compromising security and durability.

The one-way locking push nut **22** is preferably chemically or otherwise bonded to the end **20a** of the slide-on expansion tube **20**. The bonded ends preferably have a slotted 45 degree chamfer radius that produce a greater bonding area between each part. This greater bonding area gives the one-way locking push nut **22** rigidity and strength, while giving the slide-on expansion tube **20** the needed bonding strength to effectively compress or stretch/elongate and also to prevent it from twisting/turning when a torque is applied to the specially keyed bolt **10**.

In a preferred embodiment, the one-way locking push nut **22** is made of spring steel and is arranged with an approximately 45 degree chamfer radius that is slotted in four equally spaced places. In one preferred embodiment, the slotted 45 degree chamfer radius forms an approximate 0.190 inch diameter hole at its center. The 0.190 inch diameter center hole is sized to form an interference fit over the flanged bolt-retaining plug's 0.200 inch diameter metal cylindrical member **12a**. The locking push nut **22** is a one way nut. The nut's slotted 45 degree chamfer radius is designed to flex around and over the flanged bolt-retaining plug's 0.200 inch diameter cylindrical member **12a** when the nut is

pushed forwards onto the same. After the one-way locking push nut **22**, which is bonded to the slide-on expansion tube **20**, has been installed over the cylindrical member **12a**, the nut's slotted 45 degree chamfer radius hole's inner edge will dig/grab into the outer diameter of cylindrical member **12a** when the slide-on expansion tube **20** is urged in the direction opposite the one-way nature of the nut **22**, e.g., by pulling on the flange **12b**. The harder an individual tries to separate the slide-on expansion tube **20** from the flanged bolt-retaining plug **12**, the more the one-way locking push nut's 45 degree chamfer radius will dig and/or grab into the cylindrical member **12a**.

The outside diameter of the one-way locking push nut **22** is preferably sized to cover the entire outer diameter of the slide-on expansion tube **20**. If an unauthorized individual attempts to obtain access to the firearm by breaking away the flange **12b** and damaging the petroleum resistant polymer synthetic elastomer material that the slide-on expansion tube **20** is made out of, the one-way locking push nut's, which is pressing against the portion of the flange remaining after the break-away (see, e.g., the above description), will create a steel barrier at the muzzle of the firearm. This barrier will prevent an unauthorized individual from damaging the barrel plug assembly **A** to the point where it could be forcibly removed from the barrel.

One preferred embodiment of the hand ratcheting wrench assembly **B** is shown in FIGURES **3A-D**. The illustrated hand ratcheting wrench assembly **B** has multiple features. It is used to effect the installation the barrel plug assembly **A** in the bullet exit end/muzzle of a gun barrel, and it also is used to effect quick and easy removal of the barrel plug assembly **A** from the weapon's barrel (i.e., de-installation of the plug assembly **A**). In addition, the wrench assembly **B** serves as a torque limiter, a ratchet, an extraction rod retraction lock, an extraction rod extension lock, and as a holder/attachment point for the barrel plug assembly **A**.

The lower handle mount **50** is used to hold the barrel plug assembly **A** for easy installation and removal. As indicated above, the wrench assembly **B** is selectively engaged with the plug assembly **A** via the lower handle mount **50**

which has a flange receiving portion **50a** that mates with the flange **12b** of the plug assembly **A**. The flange receiving portion **50a** mates with the flange **12b** such that the relative rotational orientation therebetween remains fixed so long as the wrench assembly **B** and the plug assembly **A** are engaged. In a preferred embodiment, during the installation and removal process, three mating sides **52a-c** (best seen in FIGURE **1A** and **1C**) of the two combined parts will prevent the rest of the barrel plug assembly **A** from rotating when a torque is applied to the bolt **10**.

Preferably, the flange **12b** and the flange receiving portion **50a** of the lower handle mount **50** have a close tolerance fit such that when the flange **12b** is properly seated in the receiving portion **50a** of the lower handle mount **50**, an opening **56** is aligned along the longitudinal axis **z** with the bore of the flanged bolt-retaining plug **12** and the head **10b** of the bolt **10** housed therein. In this manner, the flange receiving portion **50a** of the lower handle mount **50** aligns and/or centers the wrench assembly **B** with the flanged bolt-retaining plug **12** so that the wrench's extraction rod **90** can easily and quickly be extended and/or retracted through the opening **56** for accurate selective engagement with the head **10b** of the bolt **10** which is recessed in the flanged bolt-retaining plug **12**.

The extraction rod **90** is aligned and/or guided through a hollow shaft **58** (best seen in FIGURES **3B** and **3C**) in the lower handle mount **50** which terminates in the opening **56**. Preferably, the shaft **58** and opening **56** are slip fit toleranced so that the extraction rod **90** can slide longitudinally therethrough and rotate therein with only a minor end play or deviation from the center line or axis **z**. A close tolerance assures that the extraction rod **90** will be properly aligned with the head **10b** of the bolt **10** located in the flanged bolt-retaining plug **12**.

Elbow shaped tabs **54** form a slot into which the flange **12b** is laterally slid or otherwise radially received with respect to the axis **z**. When the wrench and plug assemblies are engaged with one another (see, e.g., FIGURE **1A**), the tabs **54** wrap around the flange **12b** restricting it from longitudinal separation from the lower handle mount **50** and hence the wrench assembly **B**. Moreover, when flange **12b** is properly engaged with and/or seated in the receiving portion

50a of the lower handle mount **50** and the extraction rod **90** is in the extended position (as shown in FIGURE 3C), the extraction rod **90** extends through the opening **56** and into the bore of the flanged bolt-retaining plug **12** such that the plug **12** (and hence the plug assembly **A**) is restricted from sliding out of the slot laterally or radially with respect to the axis **z**. Accordingly, when the extraction rod **90** is extended, the plug and wrench assemblies are effectively locked together inasmuch as the tabs **54** restrict the flange **12b** from being longitudinally disengaged from the lower handle mount **50** and the extraction rod **90** extending into the bore of the flanged bolt-retaining plug **12** restricts the plug **12** from being laterally disengaged from the lower handle mount **50**. This locking feature permits the barrel plug assembly **A** and the hand ratcheting wrench assembly **B** to work as one assembly, and therefore makes the installation and removal of the barrel plug assembly **A** a simple, one handed procedure. In addition, if the two assemblies are left together, in the locked position, when the barrel plug assembly **A** is not installed in a gun, the two assemblies will not become separated and one will not become lost or separated from the other when stored away.

An upper portion **60** of the wrench assembly **B** is defined by three parts, namely, an inner retaining disk **62**, a housing drum **64** and a housing cap **66**, which collectively house or contain the wrench assembly components or parts numbered with reference numerals **80** through **110**. The housing drum **64** is sandwiched between the inner retaining disk **62** and the housing cap **66** which are secured to one another via a plurality of screws **68** or other like fasteners. Preferably, the lower handle mount **50**, the inner retaining disk **62**, the housing drum **64** and the housing cap **66** are formed or made from a suitably strong, hard, rigid and/or durable material, such as, aluminum or other metal or like material.

The upper portion **60** and the lower handle mount **50** are joined so as to be freely rotatable about the central **z** axis with respect to one another. Preferably, as shown, a plurality of set screws **70** extend through the housing drum **64** into a circumferential channel **59** formed in the end of the lower handle

mount which is arranged inside the end of the housing drum **64** opposite the housing cap **66**. In this manner, the upper portion **60** and lower handle mount **50** are joined together while being free to rotate about the **z** axis relative to one another.

5 The lower hand mount **50** is used to selectively secure the extraction rod **90** from unauthorized use and/or tampering. That is to say, to make the ratcheting wrench assembly **B** tamper resistant and/or to provide additional security, a user may choose to retract the extraction rod **90** upward into the lower hand mount **50**. Retracting the extraction rod **90** into the lower hand mount **50**
10 will protect the extraction rod **90** from being damaged if the hand ratcheting wrench assembly **B** is dropped, and will also prevent an unauthorized individual from using the hand ratcheting wrench assembly **B**. FIGURE **3B** shows the extraction rod in the retracted position, and FIGURE **3C** shows the extraction rod **90** in the extended position.

15 The extraction rod **90** is selectively moved and locked into each of the respective positions shown in FIGURES **3B** and **3C** by using a keyed push lock assembly which includes a lock cylinder **80**, a lock cylinder housing **82**, a locking lever **84**, a washer **86** and a screw **88**. As shown, the washer **86** is an external toothed lock washer, and the screw **88** is a cross recessed pan head machine
20 screw, however, alternate fasteners may be used. The screw and washer **88** and **86**, respectively, fasten the locking lever **84** to the lock cylinder **80** which is housed in the lock cylinder housing **82**.

 The lock cylinder **80** is operated with a key (not shown) that fits in a key hole **80a** (best seen in FIGURE **1B**) so as to selectively rotate within the lock
25 cylinder housing **82**. By rotating the lock cylinder **80**, the locking lever **84** fastened thereto is selectively engaged with (or disengaged from) one of two receiving slots **66a** and **66b** formed in the housing cap **66**. When cylinder **80** is rotated such that the lever **84** is disengaged from both slots **66a** and **66b**, the cylinder **80** and cylinder housing **82** are free to move longitudinally along the **z**
30 axis. When cylinder **80** is rotated and longitudinally positioned such that the lever **84** is engaged with slot **66a**, the cylinder **80** and cylinder housing **82** are locked in

the undepressed position shown in FIGURE 3B. When cylinder 80 is rotated and longitudinally positioned such that the lever 84 is engaged with slot 66b, the cylinder 80 and cylinder housing 82 are locked in the depressed position shown in FIGURE 3C.

5 In a preferred embodiment, the extraction rod 90 has a head 90a opposite the socket 90b. The head 90a of the extraction rod 90 is urged or pressed against a butt end 82a of the lock cylinder housing 82 by a compression spring 92 acting on a spring retainer 94 which is positioned between one end of the spring 92 and the head 90a of the extraction rod 90. The end of the
10 compression spring 92 opposite the spring retainer 94 pushes off a fixed interior lateral ledge or annular lip within the housing drum 64. Accordingly, the spring 92 pushes or urges the extraction rod 90 toward the lock cylinder housing 82, and biases the push lock to the undepressed position and the extraction rod 90 to the retracted position, as shown in FIGURE 3B. As the extraction rod 90 is biased
15 against the butt end 82a of the lock cylinder housing 82, the position of the extraction rod 90 is controlled by the longitudinal position of the of the push lock. When the push lock is moved into and/or locked in the depressed position, it effects the placement of the extraction rod 90 into the extended position, as shown in FIGURE 3C, and when the push lock is moved into and/or locked in the
20 undepressed position, it effects the placement of the extraction rod 90 into the retracted position, as shown in FIGURE 3B.

 With reference to FIGURES 3A, 8A and 8B, a ratchet assembly portion of the wrench assembly B allows the extraction rod 90 to be rotated in either direction using a continuous ratcheting motion to selectively tighten or
25 loosen the bolt 10. The ratchet assembly includes a ratchet slip clutch gear 100, a pair of ratchet arms 102a and 102b, corresponding ratchet arm compression springs 104a and 104b, and a ratchet arm selector 106.

 The ratchet slip clutch gear 100 has a triangular spur gear tooth pattern/profile 100b that symmetrically raps around its outer diameter. The two
30 ratchet arms 102a and 102b are positioned opposing one another about the outer diameter of the gear 100. The arms 102a and 102b are pivotally secured at

one end between the inner retaining disk **62** and a fixed interior lateral ledge or annular lip within the housing drum **64**. The opposing ends of the arms **102a** and **102b** are biased toward the toothed outer diameter of the gear **100** by their respective compression springs **104a** and **104b**. The two ratchet arms **102a** and **102b** are positioned so that they line up/mate with the triangular spur gear's tooth root diameter and edge profile.

The ratchet arm selector **106** includes a lever **106a** and a cam **106b** at opposing ends of a shaft **106c**. The selector **106** is arranged such that the lever **106a** extends out of the housing cap **66** for manipulation by the user. By flipping the lever **106a** 90 degrees to the left and/or right, a user selectively rotates the shaft **106c** (which is preferably parallel with and radially offset from the **z** axis) and the cam **106b** at the opposing end. The cam **106b** is positioned between the arms **102a** and **102b** and the gear **100** such that in accordance with the manipulation of the lever **106a** the cam **106b** effects the disengagement of one of the ratchet arms from the gear **100** and effects the engagement of the other ratchet arm with the gear **100**. Depending upon its rotational position, the cam **106b**, acting against the biasing force of one of the springs **104a** and **104b**, deflects one of the arms **102a** and **102b** about its pivot point while the undeflected arm is urged or pressed into engagement with the gear **100** by the biasing force of its compression spring.

In the following context, clockwise and counterclockwise refer to the direction of rotation when viewed from the housing cap **66** end of the wrench assembly **B**. When the lever **106a** is flipped so that the arm **102a** is pressed against the gear **100** by the spring **104a** and the arm **102b** is deflected by the cam **106b**, a continuous ratcheting motion (i.e., continuous rotation in alternating directions) applied to the upper portion **60** of the wrench assembly **B** advances the gear **100** counterclockwise. This is because, on the counterclockwise stroke applied to the upper portion **60**, the housing drum **64** and the inner retaining disk **62** rotate counterclockwise, and the arm **102a** moving therewith engages the teeth **100b** on the outer diameter of the gear **100** and the gear **100** is rotated counterclockwise. On the clockwise stroke applied to the upper portion **60**, the

housing drum **64** and the inner retaining disk **62** rotate clockwise, but the arm **102a** moving therewith does not engage the teeth **100b** on the outer diameter of the gear **100** and the gear **100** does not rotate. Rather, on the clockwise stroke, the arm **102a** is free to deflect about its pivot point against the biasing force of the spring **104a**, and so, the teeth **100b** on the outer diameter of the gear **100** deflect the arm **102a** (rather than engage with it) as the arm **102a** is dragged across them.

Conversely, when the lever **106a** is flipped so that the arm **102b** is pressed against the gear **100** by the spring **104b** and the arm **102a** is deflected by the cam **106b**, a continuous ratcheting motion applied to the upper portion **60** of the wrench assembly **B** advances the gear **100** clockwise. This is because, on the clockwise stroke applied to the upper portion **60**, the housing drum **64** and the inner retaining disk **62** rotate clockwise, and the arm **102b** moving therewith engages the teeth **100b** on the outer diameter of the gear **100** and the gear **100** is rotated clockwise. On the counterclockwise stroke applied to the upper portion **60**, the housing drum **64** and the inner retaining disk **62** rotate counterclockwise, but the arm **102b** moving therewith does not engage the teeth **100b** on the outer diameter of the gear **100** and the gear **100** does not rotate. Rather, on the counterclockwise stroke, the arm **102b** is free to deflect about its pivot point against the biasing force of the spring **104b**, and so, the teeth **100b** on the outer diameter of the gear **100** deflect the arm **102b** (rather than engage with it) as the arm **102b** is dragged across them.

Please note, FIGURE **8B** shows the cam **106b** deflecting the arm **102a** thereby preventing it from engaging with the teeth **100b** on the outer diameter of the gear **100**. Conversely, the position of the cam **106b** as shown in FIGURE **8B** does not deflect the arm **102b** thereby enabling it to selectively engage, depending on the direction of the stroke applied, with the teeth **100b** on the outer diameter of the gear **100**.

As described later herein, the rotation of the gear **100** and/or a torque associated therewith is transferred and/or applied to the extension rod **90** via a slip clutch output drive gear **108**. Accordingly, in this manner, the wrench's

ratchet assembly allows a user to drive the extraction rod **90** in either selected direction of rotation using a continuous ratcheting motion to selectively tighten or loosen the bolt **10**.

5 The combination of the ratchet slip clutch gear **100** and the slip clutch output drive gear **108** serves as a torque limiter to prevent an over application of torque to the bolt **10** which may potentially damage the same. The gear **100** preferably has a symmetrically oriented, beveled, angular, inner radial, gear tooth pattern **100a** on its transaxial face that abuts and mates with the transaxial face of gear **108** having a corresponding gear tooth pattern **108a**. The transaxial faces
10 of the gears **100** and **108** are compressed or biased together by a slip clutch compression spring **110**. Preferably, the spring **110** is a standard compression spring that is compressed between a fixed interior lateral ledge or annular lip within the housing drum **64** and the slip clutch output drive gear **108**. The compressed spring **110** urges or presses the slip clutch gear **100** and the slip
15 clutch output drive gear **108** together with a predetermined compressive force. When the compressive force is exceeded, the gears **100** and **108** will slip and rotate independently from one another.

The drive gear **108** preferably has a square or otherwise keyed center hole which receives a square or otherwise keyed portion **90c** of the extraction rod
20 **90** such that they are rotationally fixed with respect to one another. Therefore, the rotational movement and/or torque experienced by the drive gear **108** is transferred to the extraction rod **90**, and in turn, the bolt **10** when it is engaged with the extraction rod **90**.

When the barrel plug assembly **A** is being installed in a gun barrel's
25 bore by applying a continuous ratcheting motion to the upper portion **60** of the wrench assembly **B** with the selector lever **106a** in the bolt tightening position, both the ratchet slip clutch gear's and the slip clutch output drive gear's teeth **100a** and **108a**, respectively, will slip when a maximum allowable torque is exceeded. Accordingly, the torque applied to or experienced by the bolt **10** is
30 limited. The limited torque will prevent the bolt **10** from being over tightened, which could undesirably damage the bolt's threads **10a**, bushing **10c** and/or head

10b. Additionally, a user installing the safety device will not have to worry if the barrel plug assembly **A** has been properly secured in the gun barrel's bore. This is because when the gears **100** and **108** slip between each other, they preferably make a clicking sound to indicate that the proper torque has been applied. This
5 clicking sound is made when the mating, symmetrically oriented, beveled, and angular inner radial gear teeth **100a** and **108a**, slip and slide over their 90 degree vertical ledges, located along the apex of each of the gear's teeth.

When a user applying a continuous ratcheting motion to the upper portion **60** of the wrench assembly **B** with the selector lever **106a** in the bolt
10 loosening position to remove the barrel plug assembly **A** from the gun barrel's bore, the ratchet slip clutch gear **100** and the slip clutch output drive gear **108** automatically lock together. The automatic locking is achieved by using a 90 degree vertical ledge, located along the apex of each of the symmetrical oriented, beveled, and angular inner radial gear teeth. Essentially, the abutting
15 transaxial faces of the gears **100** and **108** have mating ramped teeth **100a** and **108a** which form a one-way slip clutch which will not slip when the relative rotation therebetween is in a first direction, and which will slip if a predetermined torque is exceeded when the relative rotation is in a second direction opposite the first. When the gears **100** and **108** are rotated relative to one another such
20 that their teeth **100a** and **100b** lock together or will not slip, the user will be able to apply as much torque/force as is needed to loosen the bolt **10** and stretch or elongate the barrel plug assembly **A**.

As already stated, in the center of the slip clutch output drive gear **108** is a square hole that is used as a guide and mount for the extraction rod **90**. This
25 square hole is designed to slide over the extraction rod's square body **90c**. The two parts preferably have a slip fit tolerance, so that the extraction rod **90** can slide easily through the slip clutch output drive gear's square hole, with very little backlash/rotational movement. The slip clutch output drive gear **108** is used to transfer the output torque from the hand ratcheting wrench's slip clutch to the
30 extraction rod **90**, while still allowing the extraction rod **90** to be extended and retracted from the hand ratcheting wrench assembly **B**.

Preferably, the hand ratcheting wrench **B** is used to install and remove the barrel plug assembly **A**, and without the hand ratcheting wrench **B**, the barrel plug assembly **A** cannot be properly installed or removed. When a user wants to install the barrel plug assembly **A** to secure their gun, they preferably perform the following steps.

The barrel plug assembly's flanged bolt-retaining plug **12** is slid into the lower handle mount **50** located on the bottom of the hand ratcheting wrench **B**, as shown in FIGURES **1A-1D**. The appropriate key is inserted into the lock cylinder **80** located on the top of the housing cap **66**, and the lock cylinder housing **82** is unlocked by turning the lock cylinder **80** so that the locking lever **84** is disengaged from the slot **66a** of the housing cap **66**. The user then push the lock cylinder housing **82** and the lock cylinder **80** down into the housing cap **66** so that the extraction rod **90** is pushed into the extended position and engages with the bolt **10**. The user now turns the lock cylinder **80** so that the locking lever **84** will engage with slot **66b** of the housing cap **66**, and preferably removes the key. This locks the extraction rod **90** in the extended position. Note: when the above steps are properly completed, the extraction rod **90** will engage with the bolt **10**.

The user inserts the barrel plug assembly **A**, that is now connected to the hand ratcheting wrench **B**, into the muzzle of the gun. Preferably, the plug assembly **A** is inserted all the way until the flange **12** is flush with the end of the barrel, as shown in FIGURES **6A-6E**. If not already there, the ratchet arm selector **106** is shifted into the locking or tightening position using the selector lever **106a**. While holding the lower handle mount **50** in one hand, the upper portion **60** of the wrench **B** is rotate using a continuous ratcheting motion of alternating clockwise and counterclockwise strokes. The ratchet assembly makes the installation of the barrel plug assembly **A** quick and easy.

The ratcheting rotation of the upper portion **60** of the wrench assembly **B** advances the ratchet slip clutch gear **100** in the clockwise direction thereby applying rotation and/or torque to the slip clutch output drive gear **108**, which, in turn, is transferred to the extraction rod **90** and the bolt **10** engaged therewith.

The rotation of the bolt **10** pulls the threaded rear compression base **16** (and the screw on expansion tube adapter **18**, if used) and the flanged bolt-retaining plug **12** together thereby longitudinally compressing the expansion tube **14** (and the slide-on expansion tube **20**, if used). Longitudinally compressing the expansion tubes **14** and **20** causes them to radially bulge and/or push against the walls in which each is contained, be it the gun barrel bore or the inner bore of the slide-on expansion tube **20**. In this manner, the plug assembly **A** becomes wedged inside of the gun's barrel, thereby securing the barrel plug assembly **A** in the gun barrel. Preferably, the user continues ratcheting the wrench assembly **B** until the biasing force of the compression spring **110** is overcome and the gears **100** and **108** slip past one another. A "clicking" sound is heard when the two gears **100** and **108** slip and rotate between each other signifying that the barrel plug assembly **A** has been fully tightened. If a clicking sound is not heard from the slip clutch gears **100** and **108**, the plug assembly **A** has not been fully tightened and ratcheting of the wrench **B** should continue.

Once fully tightened, the user reinserts the key in the lock cylinder **80** (if not still in the same), and unlocks the lock cylinder housing **82** by turning the lock cylinder **80** so that the locking lever **84** disengages from slot **66b** of the housing cap **66**. The user then allows the compression spring **92** to push the extraction rod **90** up into the retracted position and the lock cylinder housing **82** and the lock cylinder **80** into the undepressed position. Turning the lock cylinder **80** so that the locking lever **84** engages with slot **66a** of the housing cap **66** and removing the key, locks the push lock in the undepressed position and the extraction rod **90** in the retracted position to prevent tampering and/or use by an unauthorized individual.

The hand ratcheting wrench assembly **B** may now be slid away from the flanged bolt-retaining plug **12** while the plug assembly **A** remains properly installed in the barrel, as shown in FIGURES **5A-5E** and **7**. Preferably, the entire installation procedure can be easily completed in less than one (1) minute.

When an authorized user wants to remove the barrel plug assembly **A** from a gun's barrel to operate the gun or otherwise, they preferably perform the following steps.

5 The lower handle mount **50**, located on the bottom of the hand ratcheting wrench assembly **B**, is slid onto the flange **12b** of the flanged bolt-retainer plug **12** (as shown in FIGURES **6A-6E**), the appropriate key is inserted into the lock cylinder **80**, located on the top of the housing cap **66**, and the lock cylinder housing **82** is unlocked by turning the lock cylinder **80** so that the locking lever **84** is disengaged from the slot **66a** of the housing cap **66**. The user then
10 push the lock cylinder housing **82** and the lock cylinder **80** down into the housing cap **66** so that the extraction rod **90** is pushed into the extended position and engages with the bolt **10**. The user now turns the lock cylinder **80** so that the locking lever **84** will engage with slot **66b** of the housing cap **66**, and preferably removes the key. This locks the extraction rod **90** in the extended position. Note:
15 when the above steps are properly completed, the extraction rod **90** will engage with the bolt **10**.

If not already there, the ratchet arm selector **106** is shifted into the unlocking or loosening position using the selector lever **106a**. While holding the lower handle mount **50** in one hand, the upper portion **60** of the wrench **B** is
20 rotate using a continuous ratcheting motion of alternating clockwise and counterclockwise strokes. The ratchet assembly makes the removal of the barrel plug assembly **A** quick and easy.

The ratcheting rotation of the upper portion **60** of the wrench assembly **B** advances the ratchet slip clutch gear **100** in the counterclockwise direction
25 thereby applying rotation and/or torque to the slip clutch output drive gear **108**, which, in turn, is transferred to the extraction rod **90** and the bolt **10** engaged therewith. The rotation of the bolt **10** pushes the threaded rear compression base **16** (and the screw on expansion tube adapter **18**, if used) and the flanged bolt-retaining plug **12** apart thereby longitudinally stretching the expansion tube **14**
30 (and the slide-on expansion tube **20**, if used). Longitudinally stretching the expansion tubes **14** and **20** causes them to radially contract. In this manner, the

plug assembly **A** becomes unwedged from inside of the gun's barrel, thereby freeing it to be readily removed from the same. Preferably, the plug assembly **A** is slid or pulled from the gun barrel plug while still connected to the hand ratcheting wrench assembly **B**.

5 Preferably, to remove the hand ratcheting wrench **B** from the extracted gun barrel plug assembly **A**, the user reinserts the key in the lock cylinder **80** (if not still in the same), and unlocks the lock cylinder housing **82** by turning the lock cylinder **80** so that the locking lever **84** disengages from slot **66b** of the housing cap **66**. The user then allows the compression spring **92** to push the extraction
10 rod **90** up into the retracted position and the lock cylinder housing **82** and the lock cylinder **80** into the undepressed position. Turning the lock cylinder **80** so that the locking lever **84** engages with slot **66a** of the housing cap **66** and removing the key, locks the push lock in the undepressed position and the extraction rod **90** in the retracted position to prevent tampering and/or use by an unauthorized
15 individual.

 The hand ratcheting wrench assembly **B** may now be slid away from the flanged bolt-retaining plug **12** thereby separating it from the plug assembly **A**. Preferably, the entire removal or de-installation procedure can be easily completed in less than one (1) minute.

20 Preferably, the extraction rod **90** is formed or made from a suitably strong, hard, rigid and/or durable material, such as, hardened steel or other metal or like material. The bolt engaging end of the extraction rod's shaft and/or the socket **90b** preferably have a 0.140 inch outer diameter. When the hand ratcheting wrench assembly **B** is used to install the barrel plug assembly **A**, the
25 small diameter socket **90b** is extend out past the hand ratcheting wrench assembly's lower handle mount **50**. It centers itself within the very confined space of the flanged bolt-retaining plug **12** and mates up with the head **10b** of the bolt **10**. The extraction rod's socket **90b** and 0.140 inch outer diameter shaft preferably have close slip fit tolerances. These close slip fit tolerances enable the
30 flanged bolt-retaining plug **12** and the bolt **10** to mate/slide together with the

extraction rod's socket **90b** and 0.140 inch outer diameter shaft, with very little backlash or deviation from the center line or **z** axis.

5 In relationship to the socket **90b**, the extraction rod **90** has a, preferably, flat 0.750 inch outer diameter, flange or head **90a** that is located on the opposite end. This flange or head **90a** mates with and/or abuts the bottom end **82a** of the lock cylinder housing **82**. The flange or head **90a** permits the extraction rod **90** to rotate and move up and down within the hand ratcheting wrench assembly **B**, while securing the rod **90** so that it cannot be forcibly removed from the assembly **B**.

10 The lock cylinder housing **82** is used as a plunger, which when pushed into the housing cap **66** extends the extraction rod **90**, as shown in FIGURES **3C** and **3D**. Its position controls what position the extraction rod **90** is in. The housing is used to hold and align the lock cylinder **80** and the extraction rod **90**, while the entire push lock assembly moves/slides up and down within the housing cap **66**.
15 The lock cylinder **80** is used to manually lock the lock cylinder housing **82** in the selected position. When the lock cylinder housing **82** is in the "up" or undepressed position, it preferably protrudes above the housing cap **66**, indicating that the extraction rod **90** is in the retracted position, as shown in FIGURE **3B**. When the lock cylinder housing **82** is in the "down" or depressed position, it is preferably flush with the top of the housing cap **66**, indicating that
20 the extraction rod **90** is in the extended position, as shown in FIGURES **3C** and **3D**. The lock cylinder housing **82** preferably has a recessed blind hole located in the bottom end **82a** thereof so that the extraction rod's flat 0.750 inch outer diameter flange or head **90a** will fit into the same. The mating of these two parts
25 keeps the extraction rod **90** in alignment while the extraction rod **90** is rotating and moving up and down within the hand ratcheting wrench assembly **B**.

Preferably, the housing cap **66** has the two parallel 90 degree slots **66a** and **66b** located in an outside wall of the housing cap's lock cylinder housing's bore. These two slots are used as locking points for the lock cylinder
30 housing **82**. The lock cylinder housing **82** and the extraction rod **90** can be locked into the undepressed and the retracted positions, respectively, when the locking

lever **84** is slid/rotated into the housing cap's upper slot **66a**, located relatively nearer the top of the cap's curved surface. The lock cylinder housing **82** and the extraction rod **90** can be locked into the depressed and the extended positions, respectively, when the locking lever **84** is slid/rotated into the housing cap's lower slot **66b**, located relatively nearer the flat bottom of the housing cap **66**. The location and arrangement of the locking slots **66a** and **66b** ensure that when the push lock is properly lock into one of the two positions, the extraction rod **90** has been fully retracted or extended.

Preferably, the housing cap **66** and housing drum **64** are ergonomically shaped such that when the user places the hand ratcheting wrench assembly **B** in their hand, the palm of their hand will comfortably and easily mold around the curved top of the housing cap **66** while their fingers rest comfortably on the cylindrical surface of the housing drum **64**. This ergonomic fit enables the user to quickly, comfortably, and with a minimal amount of force, selectively install or remove the barrel plug assembly **A** from any gun barrel.

The hand ratcheting wrench assembly's housing drum **64** isolates the upper portion **60** from the lower handle mount **50**. Both of these subassemblies are isolated so that when any of the subassembly's parts are compressed, moved or rotated, these parts will not adversely affect the operation of the other parts. An example of this is when the lock cylinder housing **82** and the extraction rod **90** are locked in depressed and the extended positions, respectively, the compression spring **92** will be compressed. If the housing drum **64** is not compartmentalized, the extraction rod **90** and the compression spring **92** will push against the already compressed slip clutch compression spring **110**. This increase and/or variation in the spring's **110** compression force, will adversely affect the operation of the slip clutch, by increasing the amount of torque that is required to make the slip clutch slip. The compressed slip clutch compression spring **110** should always exert the same compression force on the ratchet slip clutch gear **100** and the slip clutch output drive gear **108** so that they will be forced together and always slip at a constant preset torque.

The housing drum **64** is the main rotating body of the hand ratcheting wrench assembly **B**. This housing drum **64** fastens onto and rotates around the lower handle mount **50**, while holding and/or housing all of the subassemblies of the wrench assembly **B**. The housing drum **64** enables the hand ratcheting wrench assembly **B** to have overall rotational movement with respect to the lower handle mount **50**, and at the same time, enable its internal components/subassemblies to move in determined independent linear and rotational directions.

With reference to FIGURE **9A**, an alternative barrel plug assembly **D** that includes an adjustable portion is shown. The adjustable barrel plug assembly allows the owner of the gun barrel safety lock to use the same lock with different guns having different barrel lengths. The alternative barrel plug assembly can be used with the hand ratcheting wrench assembly **B** described above.

The adjustable barrel plug assembly **D** includes a flanged bolt-retaining plug **212** that is similar to the bolt-retaining plug **12** described above. The bolt-retaining plug **212** is attached to an expansion tube **214**, which is similar to the expansion tube **14** described above. The expansion tube **214** attaches to a threaded rear compression base **216**, which is similar to the threaded rear compression tube **16** described above.

An extension rod assembly **224** attaches to the rear compression base **216** opposite the expansion tube **214**. The extension rod assembly **224** includes a tubular plug extension **232** that receives components to allow adjustment of the length of the extension rod assembly **224**. Referring to FIGURE **9E**, the tubular plug extension **232** also includes a threaded end **232a** that is received by the rear compression base **216**. The tubular plug extension **232** includes a central bore **234** that runs substantially the entire longitudinal length of the tubular plug extension. The central bore **234** receives a bolt **236**, which in one embodiment is a female hexagon bolt. The bolt includes an opening **236a** that can receive a key **226**, which will be described in more detail below. The opening **236a** in one embodiment receives a 1/16" hex Allen wrench, which acts as the key. The outer

diameter of the bolt **236** is such that the bolt can easily slide within the bore **234**. The bolt **236** also includes a shank **236b** having a threaded portion.

An annular sliding bolt retaining plug **238** receives the shank **236b** of the bolt **236**. The sliding bolt retaining plug **238** has a flat bearing surface **238a** (FIGURE **9B**) that is perpendicular to the longitudinal axis of the sliding bolt retaining plug and the tubular plug extension **232**. The flat bearing surface **238a** acts as a contact and compression point for the bolt **236** in that the bolt can spin against the bearing surface. The sliding bolt retaining plug **238** also includes a tapered portion **238b** spaced longitudinally from the flat bearing surface **238a**. The tapered end **238b** of the sliding bolt retaining plug attaches to a sliding expansion tube **242**.

The sliding expansion tube **242** is hollow to receive the shank **236b** of the bolt **236**. The sliding expansion tube is made from a petroleum resistant polymer synthetic elastomer material that has good compressive and/or stretching characteristics. The outer diameter of the sliding expansion tube **242** is such that it can freely move within the bore **234** and it can deform such that a friction fit between the inner surface of the bore **234** and the sliding expansion tube can be achieved when a compressive force is exerted on the sliding expansion tube. The sliding expansion tube **242** includes a first tapered end **242a** that receives the tapered portion **238b** of the sliding bolt retaining plug **238**. Because of the small size of the components, each tapered portion advantageously increases the surface area of contact between the sliding expansion tube **242** and the sliding bolt retaining plug **238** to provide a greater area for bonding between the components. The sliding expansion tube **242** also includes a second tapered end **242b** opposite the first tapered end **242a**. The second tapered end **242b** is received in a portion of a sliding extension rod **244**.

The sliding extension rod **244** includes a tapered end **244a** that is received by the second tapered end **242b** of the sliding expansion tube **242**. Because of the small size of the components, each tapered portion advantageously increases the surface area of contact between the sliding expansion tube **242** and the sliding extension rod **244**. The sliding extension rod

244 also includes a threaded bore **244b** that selectively receives the threaded shank **236b** of the bolt **236**. The outer diameter of the sliding extension rod **244** is such that it can freely move within the bore **234** of the tubular plug extension **232**. Preferably, the sliding extension rod **244**, along with the other components
5 that are received in the bore **234**, are designed with a slip fit tolerance that substantially reduces any misalignment or binding when the internal components are moved back and forth within the bore **234**.

Both the attachment between the sliding bolt retaining plug **238** and the sliding expansion tube **242** and the attachment between the sliding extension
10 rod **244** and the sliding expansion tube **242** are described as connections between tapered portions. Nevertheless, it is appreciated that the attachment between the components can be in any conventional manner. For example, the components can each include corresponding notched patterns that allow the components to connect by way of a mechanical interference.

15 As more clearly visible in FIGURE **9D**, the sliding extension rod **244** also includes a guide slot **252** that receives a guide tab **248** formed at or near the distal end of the tubular plug extension **232**. In the embodiment depicted, the guide slot **252** and the guide tab **248** are V-shaped. The sliding extension rod **244** can freely slide in and out of the bore **234** of the tubular plug extension **232**
20 without the guide tab **248** causing interference. The guide tab **248** provides a mechanical interference between the sliding extension rod **244** and the tubular plug extension **232** so that the rod **244** does not rotate when the bolt **236** is tightened.

To adjust the length of the barrel plug assembly **D**, a bolt **210**, which in
25 one embodiment is a male hexagon key bolt similar to the bolt **10** described above, is removed from the assembly. The key **226** is inserted into the assembly **D** and is received by the appropriately shaped opening **236a** of the bolt **236**. When tightened, the bolt **236** contacts the bearing surface **238a** of the sliding bolt retaining plug **238** pushing the bolt longitudinally toward the sliding extension rod
30 **244**. Meanwhile, the bolt **236** draws the sliding extension rod **244** towards the sliding bolt retaining plug **238**. Accordingly, the sliding expansion tube **242** is

compressed and deformed to engage the inner surface of the tubular plug extension **232**. The sliding expansion tube **242** is advantageously tubular in configuration to provide a larger contact or gripping area when compressed, especially when compared to conventional O-rings.

5 With reference to FIGURE **10A**, an alternative adjustable extension rod assembly **224a** is shown. In FIGURE **10A**, the bolt **210**, the plug **212**, the expansion tube **214** and the rear compression base **216** have been described above.

10 The adjustable extension rod assembly **224a** includes a tubular plug extension **262** that receives components to allow the length of barrel plug assembly to adjust. The tubular plug extension **262** includes a threaded end **262a** that is received by the rear compression base **216**. Referring to FIGURE **10C**, the tubular plug extension **262** includes a central bore **264** that runs substantially the entire longitudinal length of the tubular plug extension. The
15 central bore **264** includes a plurality of annular notches **266** formed throughout the central bore. The annular notches **266** can be equally spaced from one another.

 The central bore **264** receives a bolt **268**, which in one embodiment is a female hexagon bolt. The bolt includes an opening **268a** that can receive the
20 key **226**. The opening **268a** in one embodiment receives a 1/16" hex Allen wrench. The outer diameter of the bolt **268** is such that the bolt can easily slide within the bore **264** without falling into one of the notches **266**. The bolt **268** also includes a shank **268b** that includes threads and a tapered portion **268c** at the transition from a head of the bolt **268** to the shank **268b**.

25 The bore **264** of the tubular plug extension **262** receives a sliding extension rod **272**. The sliding extension rod **272** includes a threaded bore **272a** that receives the shank **268b** of the bolt **268**. The sliding extension rod also includes an expandable end that can selectively engage an inner surface of the tubular plug extension **262**. In the embodiment depicted in FIGURES **10A-10C**,
30 the sliding extension rod includes a flanged lip **272b** at a first end. The outer diameter of the flanged lip **272b** can adjust so that the sliding extension rod **272**

can move within the bore **264** without the flanged lip getting caught or falling into one of the notches **266**. The sliding extension rod **272** also includes two slits **272c** (only one visible) formed in the flanged lip **272b** and a portion of the rod **272** near the flanged lip. The slits **272c** are formed parallel to the longitudinal axis of the sliding extension rod **272** and allow for the radial dimension of the flanged lip **272b** to change. The sliding extension rod **272** also includes a tapered surface **272d** formed around the opening of the threaded bore **272a** and the flared lip **272b**. The tapered surface **272d** cooperates with the tapered portion **268c** of the bolt **268** such that when the bolt is tightened into the threaded bore **272a** of the sliding extension rod, the tapered portion **268c** forces the flanged lip **272b** radially outward so that the flanged lip moves into one of the notches **266** and engages the inner surface of the tubular plug extension.

The sliding extension rod **272** also includes a guide slot **278** similar to the guide slot **252** described above. The tubular plug extension **262** also includes a guide tab **276** similar to the guide tab **248** described above. The guide slot **278** and the guide tab **276** cooperate to restrict the rotational movement of the sliding extension rod **272** when the bolt **268** is rotated.

To adjust the length of the extension rod assembly **224a**, the bolt **210** is removed and the key **226** is inserted into the assembly. The key is used to tighten or loosen the bolt **268** in the threaded bore **272a**. When the bolt **268** is tightened, the tapered portion **268c** of the bolt forces the flanged lip **272b** of the sliding extension rod **272** radially outward toward the inner surface of the tubular plug extension **262** into one of the grooves **266**. When the bolt **268** is loosened, the flanged lip **272b** moves radially towards the longitudinal axis and out of one of the grooves **266**, to allow for adjustment.

With reference to FIGURES **11A** and **11B**, an alternative to the abovementioned adjustable extension rod assembly is shown. In this embodiment, the tubular plug extension **262** is similar to and can be the same as the tubular plug extension described with reference to FIGURES **10A-10C**. Also, the sliding extension rod **274** is similar to the sliding extension rod **272** described above in that it includes a bore **274a**, a flanged lip **274b**, and a pair of slits **274c**.

In this embodiment, however, the bore **274a** preferably is not threaded. Also, as more clearly visible in FIGURE **11C**, the sliding extension rod **274** includes an inner flange **274d**.

The bore **274a** receives a sliding plunger wedge **282** and a spring **284**.

5 The spring **284** biases the sliding plunger wedge **282** towards the inner flange **274d**. As seen in FIGURE **11C**, the key **226** can be inserted into the assembly to move the sliding plunger wedge **282** longitudinally away from the inner flange **274d**. With the sliding plunger wedge **282** moved away from the inner flange **274d**, the flanged lip **274b** moves toward the longitudinal axis of the sliding
10 extension rod **274** and the tubular plug extension **262**, thus away from the notches **266**. With the flanged lip **274b** retracted inwardly, the sliding extension rod **274** can be adjusted. The key **226** can then be removed and the spring **284** biases the sliding wedge plunger **282** towards the inner flange **274d**, thus radially biasing the flanged lip **274b** into one of the notches **266**.

15 With reference to FIGURES **12A-12C**, another alternative of an adjustable barrel plug assembly is disclosed. In FIGURE **12A**, the bolt **210**, the plug **212**, the expansion tube **214** and the rear compression base **216** have been described above. Also, a guide tab **276** and a guide slot **278** can be provided to keep openings **296** in alignment with opening **298b**.

20 The adjustable barrel plug assembly also includes a plug extension tube **292** having a longitudinal bore **294** (FIGURE **12C**) and a plurality of openings **296** extending through a wall of the plug extension tube **292**. The longitudinal bore **294** is similar to the bore **234** described with reference to FIGURE **9E**, in that the bore is smooth and runs substantially the entire length of
25 the plug extension tube **292**. The openings **296** can be evenly spaced and aligned with one another, as shown in FIGURE **12A**. The plug extension tube **292** also includes a threaded end **292a** that is received by the rear compression base **216**. The plug extension tube **292** receives a sliding extension rod **298**.

The sliding extension rod **298** includes a longitudinal bore **298a** that
30 receives a sliding bearing plunger wedge **306**, a ball **308** and a biasing member

312. The sliding extension rod **298** also includes an alignment opening **298b** extending through the rod that communicates with the longitudinal bore **298a**.

The sliding bearing plunger wedge **306** includes a ramp **306a** formed in a side. In one embodiment, the ramp **306a** is a half tear-drop shape. The
5 sliding bearing plunger wedge **306** also includes a bearing surface **306b** that bears against the biasing member **312**, which in the embodiment depicted is a coil spring.

The ball **308** is moves on the ramp **306a** of the sliding bearing plunger wedge **306**. The ball **308** is dimensioned to fit through the alignment opening
10 **298b** and partially into, preferably one-quarter of the way into a corresponding opening **296** in the plug extension tube **292**. To adjust the length of the barrel plug assembly, the key **226** is inserted into the assembly to bias the sliding bearing plunger wedge **306** towards a distal end of the assembly. With the sliding bearing plunger wedge **306** biased towards the distal end of the
15 assembly, the ball **308** can move on the ramp **306a** axially toward the longitudinal axis of the sliding extension rod **298**. With the ball **308** displaced toward the longitudinal axis, the sliding extension rod **298** can be moved in relation to the plug extension tube **292**. Releasing the sliding bearing plunger wedge **306** results in the ball **308** traveling on the ramp **306a** radially away from
20 the longitudinal axis and towards the opening **298b**. The sliding bearing plunger wedge **306** retains the ball **308** in the openings **298b** and **296**.

With reference to FIGURES **13A** and **13B**, bore adjusting components **C** similar to those described above (i.e., one-way locking push nut **22**, slide-on expansion tube **20** and screw-on expansion tube adapter **18**) can also attach to
25 the adjustable barrel plug assemblies described above. With such a configuration, both the barrel length and the caliber of the barrel plug assembly can be adjusted.

With reference to FIGURES **14A** and **14B**, each of the abovementioned barrel plug assemblies can include a flexible joint **322**. In the
30 embodiment depicted, the flexible joint **322** comprises a spring that fits between the rear compression base **216** and the tubular plug extension **232**. As seen, the

flexible joint **322** is received in a female receptacle on the rear compression base **216** and the tubular plug extension **232**. In alternative embodiments, the flexible joint can fit elsewhere on and in alternative manners to the assembly. The flexible joint protects the barrel plug assembly from being bent when not installed
5 in a gun.

The invention has been described with reference to the preferred embodiments. However, certain modifications and alterations are contemplated. In one instance, it is contemplated that the wrench assembly **B** could be automated, for example, with a small battery operated DC reverse polarity motor.
10 In another instance, it is contemplated that wrench assembly **B** and the barrel plug assembly **A** could be permanently joined, for example, by affixing the flange **12b** to the lower handle mount **50** or by forming the flanged bolt-retaining plug **12** and the lower handle mount **50** as single piece. In either case, if the wrench assembly **B** was forcibly tampered with, the flange bolt retaining plugs' flange
15 **12b** (which is now joined to or part of the lower handle mount **50**) would still break-away at gap **12b'** leaving the rest of the plug assembly **A** securely installed in the guns' barrel. Obviously, other modifications and alterations will occur to others upon reading and understanding the preceding detailed description. It is intended that the invention be construed as including all such modifications and
20 alterations insofar as they come within the scope of the appended claims or the equivalents thereof.